



PRODUCT SPECIFICATION

AISCAN ACOPLAST

TYPE	COMPOSITION	Ø OUT mm	TOLERANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	Nº SPIRAL	SPIRAL SECUENCE	LAYERS	RADIUS MIN. CURVATURE mm	Nº TIES
AISCAN-ACOPLAST-40	POLYOLEFINE	40	+0 -0,4	30,5	100	+2 -1	55	11-11-11-11-11	5	160	4
AISCAN-ACOPLAST-50	"	50	+0 -0,5	40	100	+2 -1	48	8-8-8-8-8-8	6	200	4
AISCAN-ACOPLAST-63	"	63	+0 -0,6	50	100	+2 -1	40	8-8-8-8-8	5	252	6
AISCAN-ACOPLAST-90	"	90	+1,7 -0	73	75	+2 -1	28	6-5-6-5-6	5	252	6
AISCAN-ACOPLAST-110	"	110	+2 -0	88	50	+1,5 -1	17,6	5-4-5-3+4/6	4	252	6
AISCAN-ACOPLAST-160	"	160	+2,9 -0	130	50	+1,5 -1	14,2	4-3-4-3-4+1/6	4	400	6
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2014/05	7	EP-AC									

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-22. EXCEPT WITH REGARD TO PARAGRAPHS 8 DIMENSIONS AND 10.4 ESSAY BENDING TO COMPLY WITH THE NORM IEC 61386-24

CODE:	232222540010
CRUSHING STRENG:	>320 N
IMPACT RESISTANCE:	>2J at -5°C
OPERATING TEMPERATURE RANGE:	-5+90°C
CURVABLE	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	NO
COLOUR:	GREY RAL. 7035

CHARACTERISTICS LABEL

Each label indicates:

Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked.

ACCESORY TUBE

TYPE "AISCAN-A"

ACCORDING TO STANDARD UNE-EN 50267-2-2 [old UNE-21-147(2)/IEC-754(2)] about "Determination of the degree of acidity of gases for materials by measuring pH and conductivity". WITH NYLON GUIDE

NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.