



PRODUCT SPECIFICATION

FLEXIBLE CURVES

TYPE	COMPOSITION	Ø OUT mm	TOLERANCE mm	Ø INS. mm	LENGTH mm	TOLER. mm	INSIDE RADIUS (+-5)	ANG.º	CURVES / BOX
AISCAN-CF-20	FLEXIBLE PVC	20	+0 -0,3	13	170	+5	100	VARIABLE	600
AISCAN-CF-25	“	25	+0 -0,3	17	202	+5	115	VARIABLE	300
AISCAN-CF-32	“	32	+0 -0,3	23	224	+5	125	VARIABLE	200
AISCAN-CF-40	“	40	+0 -0,4	29	302	+5	170	VARIABLE	90
AISCAN-CF-50	“	50	+0 -0,4	37	344	+5	190	VARIABLE	40
EDITION DATE	EDITION NUMBER	CARD NUMBER							
2014/05	3	EP-CF							

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-22		CHARACTERISTICS LABEL <i>Each label indicates:</i>	USE
CODE:	432132540010	Each curve specifies the type, nominal, CE marking, date and hour	IN THE TYPE TUBES: "PIPES FIXED IN SURFACE"
CRUSHING STRENG:	>1250 N		
IMPACT RESISTANCE:	>2J at -5°C		
OPERATING TEMPERATURE RANGE:	-5+60°C		
RIGID	YES		
DIELECTRICAL RIGIDITY:	>2000 V		
ISOLATION RESISTANCE:	>100 MOhm		
EXTERNAL INFLUENCES:	IP54		
FLAME PROPAGATE:	NO		
COLOUR:	BLACK / GREY		

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.-