



PRODUCT SPECIFICATION

AISCAN DP Light (Coils)

TYPE	COMPOSITION	Ø OUT mm	TOLERANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	Nº SPIRAL	SPIRAL SEQUENCE	LAYERS	RADIUS MIN. CURVATURE mm	Nº TIES	IMPACT RESISTANCE AT -5°C. (J) *
DP-40	POLYOLEFINE	40	+0,8-0	30,5	100 50	+2 -1	55 32,25	11-11-11-11-11 7-6-7-6-6+1/4	5	200	4	3
DP-50	“	50	+1 -0	40	100 50	+2 -1	48 27	8-8-8-8-8-8 5-4-5-4-5-4	6	200	4	3
DP-63	“	63	+1,2-0	48,5	100 50	+2 -1	40 25	8-8-8-8-8 5-5-5-5-5	5	252	6	6
DP-75	“	75	+1,4-0	56	100	+2 -1	35	6-6-6-6-6-5	6	252	6	6
DP-90	“	90	+1,7-0	73	75	+2 -1	28	6-5-6-5-6	5	252	6	6
DP-110	“	110	+2-0	88	50	+1,5 -1	17,6	5-4-5-3+4/6	4	252	6	12
DP-125	“	125	+2,3-0	101	50	+1,5 -1	16	4-4-4-4	4	400	6	12
DP-160	“	160	+2,9-0	130	50	+1,5 -1	14,2	4-3-4-3+1/6	4	400	6	15
DP-200	“	200	+3,6 -0	164	50	+1,5 -1	12,1	3-3-3-3+1/6	4	400	6	15
EDITION DATE	EDITION NUMBER	CARD NUMBER										
2014/05	8	EP-DRL										



CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-24

MULTIPLE WALL TUBE (Inside smooth, outside corrugated)	
TYPE: L (Light)	
CRUSHING STRENGTH:	>250 N
IMPACT RESISTANCE:	Light *
CURVABLE	YES
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	YES
COLOUR:	ORANGE

CHARACTERISTICS LABEL

Each label indicates:

Type, nominal, number of meter, standard UNE-EN applied, use light, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

The tube goes marking every 2 meters with a code that indicates: brand, type, nominal and use.

ACCESSORY TUBE

TYPE "AISCAN-MP"

WITH NYLON GUIDE INCLUDED.

NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS ADVERTISEMENT.