



# PRODUCT SPECIFICATION

## AISCAN DP Normal (Rods)

TYPE	COMPOSITION	Ø OUT mm	TOLERANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	SLEEVES	LABELS	TUBES MALLET	Nº TIES	RODS PALLET	IMPACT RESISTANCE AT -5°C. (J) *
DP-90	POLYOLEFINE	90	+1,7 -0	73	6	+20 -5	1	1	7	4	115	20
DP-110	“	110	+2 -0	88	6	+20 -5	1	1	5	4	76	28
DP-125	“	125	+2,3 -0	101	6	+20 -5	1	1	3	4	60	28
DP-160	“	160	+2,9 -0	130	6	+20 -5	1	1	3	4	33	40
DP-200	“	200	+3,6 -0	164	6	+20 -5	1	1	--	--	20	40
EDITION DATE	EDITION NUMBER	CARD NUMBER										
2014/05	7	EP-DPNB										



### CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-24

MULTIPLE WALL TUBE (Inside smooth, outside corrugated)	
TYPE: N (NORMAL)	
CRUSHING STRENGTH:	>450 N
IMPACT RESISTANCE:	Use Normal *
RIGID	YES
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	YES
COLOUR:	ORANGE

### CHARACTERISTICS LABEL

*Each label indicates:*

Type, nominal, number of meter, standard UNE-EN applied, use light, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

The tube goes marking every 2 meters with a code that indicates: brand, type, nominal and use.

### ACCESSORY TUBE

**TYPE "AISCAN-MP"**

**NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS ADVERTISEMENT.**