



PRODUCT SPECIFICATION

AISCAN K

TYPE	COMPOSITION	Ø OUT mm	TOLER. ANCE. mm	Ø INS. mm	LENGTH m	TOLER. mm	SLEEVES	LABELS	TUBES MALLETT	Nº TIES	TYPE
AISCAN-K-63	RIGID PVC	63	+,-0,5	47	4000	+10 -5	1	50	1	10	4
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2014/05	3	EP-K									

TUBE NOT SUITABLE FOR ELECTRICAL INSTALLATIONS OVER 49 V.

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-21		CHARACTERISTICS LABEL <i>Each label indicates:</i>
CODE:	105/124500	Type, nominal, number of meters, storage and handling instructions, Barcode EAN-13, date, number of control and production line and display " TUBE NOT SUITABLE FOR INSTALLATIONS OVER A 49" SPECIFIED IN EACH TUBE: type, nominal, applicable standard, code, date, time and production line and an indication of " TUBE NOT SUITABLE FOR INSTALLATIONS OVER A 49"
INSULATION		
SMOOTH		
VERY LIGHT		
CRUSHING STRENG:	>125 N	
IMPACT RESISTANCE:	>0,5J at -5°C	
OPERATING TEMPERATURE RANGE:	-5+60°C	
RIGID	YES	
DIELECTRICAL RIGIDITY:	>2000 V	
ISOLATION RESISTANCE:	>100 MOhm	
EXTERNAL INFLUENCES:	IP54	
FLAME PROPAGATE:	NO	
COLOUR:	BLACK	

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.-