



PRODUCT SPECIFICATION

AISCAN RHF-B

TYPE	COMPOSITION	Ø OUT mm	TOLER. ANCE. mm	Ø INS. mm	LENGTH m	TOLER. mm	THREAD	THREAD LENGTH MM.	SLEEVES
AISCAN-RHF-B-63	HALOGEN-FREE TERMOPLASTIC	63	+0 -0,6	52	3000	+10 -5	1	5	3
AISCAN-RHF-B-90	“	90	+1,7 -0	67	3000	+10 -5	1	5	3
EDITION DATE	EDITION NUMBER	CARD NUMBER							
2014/05	4	EP-RHF-B							

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-21

CODE:	443212540010
CRUSHING STRENG:	>1250 N
IMPACT RESISTANCE:	>6J at -15°C
OPERATING TEMPERATURE RANGE:	-15+90°C
RIGID	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	NO
COLOUR:	GREY RAL. 7035

CHARACTERISTICS LABEL

Each label indicates:

Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked."

ACCORDING TO STANDARD UNE-EN 50267-2-2 [old UNE-21-147(2)/IEC-754(2)] about "Determination of the degree of acidity of gases for materials by measuring pH and conductivity".
ACCORDING TO STANDARD UNE-EN 21031-15:2008 "Determination of halogens. Elementary test".

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT-