



# PRODUCT SPECIFICATION

## TERMOFLEX

TYPE	COMPOSITION	Ø OUT mm	TOLERANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	Nº SPIRAL	SPIRAL SECUENCE	LAYERS	RADIUS MIN. CURVATURE mm	Nº TIES
TERMOFLEX-13,5	POLIPROPILENE	18,3	+0,5	12,7	100	+2 -1	77	9-8-9-8-9-8-9-8-9	9	60	4
TERMOFLEX-16	POLIPROPILENE	21,0	+0,5	15,2	100	+2 -1	72	8-8-8-8-8-8-8-8-8	9	75	4
TERMOFLEX-19	POLIPROPILENE	24,5	+0,5	18,5	50	+2 -1	42	7-7-7-7-7-7	6	75	4
TERMOFLEX-23	POLIPROPILENE	28,1	+0,6	21,7	50	+2 -1	42	6-6-6-6-6-6-6-6	7	96	4
TERMOFLEX-29	POLIPROPILENE	34,2	+0,6	27,5	50	+2 -1	35	5-5-5-5-5-5-5-5	7	160	4
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2007/12	5	EP-TR									

**TUBE NOT APPLICABLE FOR ELECTRICAL INSTALLATIONS (Marking and protecting water pipes)**

CHARACTERISTICS ACCORDING TO STANDARD UNE. 20334		CHARACTERISTICS LABEL
CODE:	195/424500	<i>Each label indicates:</i>  Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.
CORRUGATED		
VERY LIGHT		
IMPACT RESISTANCE:	>0,5J at -25°C	
CURVABLE	YES	
OPERATING TEMPERATURE RANGE:	-15 +90°C	
CRUSHING STRENG:	>125N	
EXTERNAL INFLUENCES:	IP54	
FLAME PROPAGATE:	YES	
COLOUR:	RED RAL 3020 BLUE RAL 5015	

SIZE ACCORDING TO STANDARD UNE.20333

**- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.-**