

# AENOR

## AENOR Product Certificate Conduit systems for cable management



**030/002223**

AENOR certifies that the organization

**AISCAN, S.L.**

registered office CM CABESOLS, S/N 03410 BIAR (Alicante - España)

supplies Rigid conduit systems for cable management

in compliance with UNE-EN 61386-1:2008 (EN 61386-1:2008)  
UNE-EN 61386-1:2008 ERRATUM:2010  
UNE-EN 61386-21:2005 (EN 61386-21:2004)  
UNE-EN 61386-21:2005/A11:2011 (EN 61386-21:2004/A11:2010)

References Specified in Annex to the Certificate

Production site CM CABESOLS, S/N 03410 BIAR (Alicante - España)

Certification scheme In order to grant this Certificate, AENOR has tested the product and has verified the quality system implemented for its manufacture. AENOR performs these tasks periodically while the Certificate has not been cancelled, in accordance with Specific Rules RP 030.12.

This certificate supersedes 030/002223, dated 2015-12-03

First issued on 2010-12-03  
Modified on 2017-12-12  
Validity date 2020-12-03

A handwritten signature in blue ink, appearing to read 'Rafael Garcia Meiro'.

Rafael GARCÍA MEIRO  
Chief Executive Officer

Original Electronic Certificate

# AENOR

## AENOR Product Certificate Conduit systems for cable management

030/002223

### Annex to Certificate

Trade mark: AISCAN

Type Ref.	Type	Nominal diameters	Inside diameters	Classification codes	Accessories	Colours	Additional information
TME	Metallic	16-20-25-32-40-50-63 mm.	>14-18-23-29,6-37,6-47,2-60 mm	555711542010	Sleeves; Ref. MTME; Bends: Ref. CME : 16-20-25-32-40-50-63 mm.	Zincado	Connectable
TMR	Metallic	16-20-25-32-40-50-63 mm.	>13,6-17,6-21,5-29,2-37,2-47,2-59,6 mm.	555711542010	Sleeves: Ref. MTMR; Internal metal sleeve: Ref. MMI; coupling metal: Ref. MMA; Short coupling metal sleeve; Bends: Ref. CMR.	Zincado	Threadable.; bend 180°, ref. CMR 180 (32-40-50 mm.)

Classification codes: First digit - Resistance to compression. - Second digit - Resistance to impact. - Third digit - Minimum permanent application and installation temperature. - Fourth digit - Maximum permanent application and installation temperature. - Fifth digit - Resistance to bending. - Sixth digit - Electrical properties. - Seventh digit - Resistance to ingress of solid objects. - Eighth digit - Resistance to ingress of water. - Ninth digit - Resistance to corrosion. - Tenth digit - Tensile strength. - Eleventh digit - Resistance to flame propagation. - Twelfth digit - Suspended load capacity

Original Electronic Certificate

First issued on 2010-12-03  
Modified on 2017-12-12  
Validity date 2020-12-03

AENOR INTERNACIONAL S.A.U.  
Génova, 6. 28004 Madrid. España  
Tel. 91 432 60 00.- www.aenor.com

Product certification body accredited by ENAC, number 01/C-PR275