

AENOR

AENOR Product Certificate Conduit systems for cable management



030/002312

AENOR certifies that the organization

AISCAN, S.L.

registered office	CM CABESOLS, S/N 03410 BIAR (Alicante - España)
supplies	Rigid conduit systems for cable management
in compliance with	UNE-EN 61386-1:2008 (EN 61386-1:2008) UNE-EN 61386-1:2008 ERRATUM:2010 UNE-EN 61386-21:2005 (EN 61386-21:2004)
References	Specified in Annex to the Certificate
Production site	CM CABESOLS, S/N 03410 BIAR (Alicante - España)
Certification scheme	In order to grant this Certificate, AENOR has tested the product and has verified the quality system implemented for its manufacture. AENOR performs these tasks periodically while the Certificate has not been cancelled, in accordance with Specific Rules RP 030.12.
	This certificate supersedes 030/002312, dated 2013-01-22
First issued on	2013-01-22
Modified on	2017-12-12
Validity date	2023-01-22

A handwritten signature in blue ink, appearing to read 'Rafael Garcia Meiro'.

Rafael GARCÍA MEIRO
Chief Executive Officer

Original Electronic Certificate

AENOR

AENOR Product Certificate Conduit systems for cable management

030/002312

Annex to Certificate

Trade mark: AISCAN

Type Ref.	Type	Nominal diameters	Inside diameters	Classification codes	Accessories	Colours
AISCAN-BGE	Non metallic	16-20-25-32-40-50-63 mm.	>10,5-14-18-24,5-31,5-40,5-52 mm.	43211254; -; 010	sleeve: Ref- AISCAN-MP ; bends Ref. AISCAN-B	Grey
AISCAN-BGR	Non metallic	16-20-25-32-40-50-63 mm.	>10,5-14-18-24,5-31,5-40,5-52 mm.	43211254; -; 010	sleeve: Ref- AISCAN; bends Ref. AISCAN-B	Grey
AISCAN-BNE	Non metallic	16-20-25-32-40-50-63 mm.	>10,5-14-18-24,5-31,5-40,5-52 mm.	43211254; -; 010	sleeve: Ref- AISCAN-MP ; bends Ref. AISCAN	Black
AISCAN-BNR	Non metallic	16-20-25-32-40-50-63 mm.	>10,5-14-18-24,5-31,5-40,5-52 mm.	43211254; -; 010	sleeve: Ref- AISCAN; bends Ref. AISCAN	Black
EXTRADUR	Non metallic	16-20-25-32-40-50-63 mm.	>10,5-14-18-24,5-31,5-40,5-52 mm.	43211254; -; 010	sleeve: Ref- AISCAN; bends Ref. AISCAN	Black
EXTRADUR G°9	Non metallic	16-20-25-32-40-50-63 mm.	>10,5-14-18-24,5-31,5-40,5-52 mm.	43211254; -; 010	sleeve: Ref- AISCAN; bends Ref. EXTRADUR G°9	Grey

Classification codes: First digit - Resistance to compression. - Second digit - Resistance to impact.- Third digit-Minimum permanent application and installation temperature. - Fourth digit-Maximum permanent application and installation temperature. - Fifth digit- Resistance to bending. - Sixth digit - Electrical properties. - Seventh digit-Resistance to ingress of solid objects. - Eight digit- Resistance to ingress of water.- Ninth digit-Resistance to corrosion.- Tenth digit- Tensile strength.- Eleventh digit - Resistance to flame propagation.- Twelfth digit -Suspended load capacity

First issued on 2013-01-22
Modified on 2017-12-12
Validity date 2023-01-22

Original Electronic Certificate

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.com

Product certification body accredited by ENAC, number 01/C-PR275